



Carbonio / Nero



Cremisi / Rosso Rocket / Grigio Tortora

SPECIFICHE TECNICHE **Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.**

TELAIO	S-Works Tarmac SL6, FACT 12r carbon fiber, Rider-First Engineered™, OSBB, clean routing, internally integrated seat clamp, 12x142mm thru-axle, flat-mount disc
FORCELLA	S-Works FACT 12r carbon, 12x100mm thru-axle, flat-mount disc
ATTACCO	S-Works SL, alloy, titanium bolts, 6-degree rise
NASTRO	Roubaix S-Wrap
SELLA	Body Geometry S-Works Power, carbon fiber rails, carbon fiber base
REGGISELLA	S-Works FACT carbon Tarmac seatpost, 20mm offset
FRENO ANT.	Shimano Dura-Ace R9170, hydraulic disc
FRENO POST.	Shimano Dura-Ace R9170, hydraulic disc
COMANDI	Shimano Dura-Ace Di2 Disc R9170
DERAGL. ANT.	Shimano Dura-Ace Di2 R9150, braze-on
CAMBIO POST.	Shimano Dura-Ace Di2 R9150, 11-speed
CASSETTA	Shimano Dura-Ace R9100, 11-speed, 11-30t
GUARNITURA	S-Works Power Cranks, dual-sided power measurement, +/- 1.5% accuracy
INGRANAGGI	52/36T
MOVIM. CENTR.	OSBB, CeramicSpeed bearings
CATENA	Shimano Dura-Ace, 11-speed
RUOTA ANT.	Roval CLX 50 Disc, carbon, tubeless-ready, Win Tunnel Engineered, 50mm depth, CeramicSpeed bearings, 21h
RUOTA POST.	Roval CLX 50 Disc, carbon, tubeless-ready, Win Tunnel Engineered, 50mm depth, DT Swiss 240 internals, CeramicSpeed bearings, 24h
PNEUMATICO ANT.	Turbo Cotton, 320 TPI, 700x26mm
PNEUMATICO POST.	Turbo Cotton, 320 TPI, 700x26mm

S-WORKS TARMAC DISC SRAM ETAP

	44	49	52	54	56	58	61
Stack (mm)	500	514	527	544	565	591	612
Reach (mm)	365	375	380	384	395	402	408
Lunghezza Tubo sterzo (mm)	105	115	126	143	163	190	210
Angolo sterzo (degrees)	70.5	71.75	72.5	73	73.5	73.5	74
Altezza Mov. Centr. (mm)	266	266	266	268	268	268	268
BB Drop (mm)	74	74	74	72	72	72	72
Trail (mm)	71	63	58	58	55	55	52
Lunghezza intera forcella (mm)	363	363	363	363	363	363	363
Offset forcella / Rake (mm)	47	47	47	44	44	44	44
Avancorsa (mm)	571	574	577	579	591	606	613
Lunghezza Batticatena (mm)	410	410	410	410	410	410	410
Interasse (mm)	969	973	975	978	990	1005	1012
Lunghezza Tubo Orizz. virtuale (mm)	490	508	531	540	562	577	595
Altezza standover (mm)	730	740	755	775	795	826	850
Lunghezza piantone (mm)	400	431	462	461	501	522	553
Angolo Sella (degrees)	76	75.5	74	74	73.5	73.5	73
Lunghezza Pedivella (mm)	165	165	170	172.5	172.5	175	175
Larghezza Manubrio (mm)	360	380	400	420	420	440	440
Lunghezza attacco manubrio (mm)	70	80	90	100	100	110	110
Larghezza sella (mm)	155	155	155	143	143	143	143
Lunghezza reggisella (mm)	320	320	320	380	380	380	380

ART. NR.	DESCRIZIONE	COLORE	MISURA
90620-0249	SW TARMAC SL6 SW DISC Di2	Carbonio / Nero	49
90620-0252			52
90620-0254			54
90620-0256			56
90620-0258			58
90620-0261			61
90620-0144	SW TARMAC SL6 SW DISC Di2	Cremisi / Rosso Rocket / Grigio Tortora	44
90620-0149			49
90620-0152			52
90620-0154			54
90620-0156			56
90620-0158			58
90620-0161			61